
# A2543 DU Box CONNECTOR

### 2.54mm Pitch/Disconnectable Crimp style connectors





- Secure locking structure
- Low insertion force
- Suction area for picking up
- Improvement of engagement with prying

#### Specifications:\_

- Current rating: 3.0 A / AC,DC (AWG #22)
- Voltage rating: 250 V AC/DC
- Temperature range: -40°C ~+105°C (including temperature rise in applying)
  - electrical current)
- Contact resistance: Initial value/ 20m Ω max
- Insulation resistance: 1000 M  $\Omega$  min

Withstanding voltage: 1500 VAC/minute Applicable wire: Conductor size/ AWG#26~#22 Insulation O.D./ 1.00 to 1.63 mm

- \* Compliant with RoHS2/ REACH
- Refer to "General Instruction and Notice when using Terminals and Connectors"
- \* Contact CSG for details

#### Material:


Housing: PPO/ PBT/ PA66/UL94-V0;Color:Black Terminal: Bass/ Phosphor/ Tin-plated/ Gold-Plated G/F

Note: 1. The above figure is the figure viewed from the connector mounting side.


- 2. Tolerances are non-cumulative: ±0.08 mm for all centers.
- 3. The dimensions above should serve as a guideline. Contact CSG for details.



# A2543 DU Box





## 働⊕⊕⊕⊕⊕⊕





14.00-

	Dimension mm		
CSG PART NO.	Α	В	Q'ty/BAG
A2543HF001AAXX0032		2.54	1000PCS
A2543HF002AAXX0032	2.54	5.08	1000PCS
A2543HF003AAXX0032	5.08	7.62	1000PCS
A2543HF004AAXX0032	7.62	10.16	1000PCS
A2543HF005AAXX0032	10.16	12.70	1000PCS
A2543HF006AAXX0032	12.70	15.24	1000PCS
A2543HF007AAXX0032	15.24	17.78	1000PCS
A2543HF008AAXX0032	17.78	20.32	1000PCS
A2543HF009AAXX0032	20.32	22.86	1000PCS
A2543HF010AAXX0032	22.86	25.40	1000PCS
A2543HF011AAXX0032	25.40	27.94	1000PCS
A2543HF012AAXX0032	27.94	30.48	1000PCS
A2543HF013AAXX0032	30.48	33.02	1000PCS
A2543HF014AAXX0032	33.02	35.56	1000PCS
A2543HF015AAXX0032	35.56	38.10	1000PCS
A2543HF016AAXX0032	38.10	40.64	1000PCS
A2543HF017AAXX0032	40.64	43.18	1000PCS
A2543HF018AAXX0032	43.18	45.72	1000PCS
A2543HF019AAXX0032	45.72	48.26	1000PCS
A2543HF020AAXX0032	48.26	50.80	1000PCS
A2543HF021AAXX0032	50.80	53.24	1000PCS
A2543HF022AAXX0032	53.24	55.88	1000PCS
A2543HF023AAXX0032	55.88	58.42	1000PCS
A2543HF024AAXX0032	58.42	60.96	1000PCS
A2543HF025AAXX0032	60.96	63.50	1000PCS
A2543HF026AAXX0032	63.50	66.04	1000PCS
A2543HF027AAXX0032	66.04	68.58	1000PCS
A2543HF028AAXX0032	68.58	71.12	1000PCS
A2543HF029AAXX0032	71.12	73.66	1000PCS
A2543HF030AAXX0032	73.66	76.20	1000PCS
-			










-3.90-


8.30






CSG


## A2543 DU Box




CSG

## A2543 DU Box










SECTION B-B				

CSG PART NO.	Wire Range	Insulation O.D.	Q'ty/Ree
A2543F0BTP032	AWG#22~#26	1.63mm(max)	10000PCS
A2543F0BGF032	AWG#22~#26	1.63mm(max)	10000PCS



CSG